

FSE 308

The Plug & Play receiver for chain hoists!

Top features:

Frequency management!

Integrated horn!

Compact design!

Integrated signal light!

... and much more!



**DECT
option**

Quality in Control.



FSE 308



Highlights:

Frequency management

A fully automated frequency management via DECT or 2.4 GHz technology ensures interruption-free radio operation without frequency conflicts.

Integrated horn

The FSE 308 is equipped with an integrated horn (volume: 91 dB). This ensures optimum safety at no additional costs.

Direct mounting = Plug & Play

The FSE 308 can be directly mounted onto standard chain hoists. Installation is easy and does not require any wiring effort or wear-intensive cables.

Compact design

With its extremely compact dimensions, the FSE 308 can be installed with ease on machines with limited space.

Integrated signal light

An integrated light to indicate the radio operation of the chain host comes standard with the FSE 308. Thus, the operator can conveniently save costs.

Applications:

All common standard chain hoists.



FSE 308.

Connection:

Han 10.

Further details:

- Up to 8 black / white commands + E-STOP.
- E-STOP: PL d, category 3 according to EN ISO 13849-1:2008.
- Robust plastic housing, protection class IP 65.
- Dimensions: 119 x 141 x 57 mm (4.7 x 5.5 x 2.2").
- Weight: ca. 550 g (1.2 lbs.).
- Power supply: 24 V AC, 48 – 240 V AC.
- Recommended transmitters: radiomatic® pilot, quadrix, keynote and the micron series.