

micron 5



***The classic with top functions
for diverse fields of applications!***

NEW:

**DECT
option**

High-quality HBC buttons!

Rotary switch!

Ex version!

User identification!

Vibration alarm!

... and much more!



Quality in Control.



micron 5



Highlights:



Rotary switch

The micron 5 comes standard with rotary switch plus 10 two-step HBC push buttons. The transmitter thus offers an enormous range of functions for diverse fields of applications.



Ex version (option)

The micron 5 is available in a version for Ex zones 1, 2, 21 and 22, opening up numerous additional fields of application for the transmitter.



User identification (option)

The HBC Smart Card protects the control from unauthorized use. It enables the blocking of safety-relevant functions for non-authorized personnel as well as the storage of useful operational data.



Vibration alarm

This function is triggered by low battery level. As an option, it can be used for feedback information such as warnings of impending overloads.



Feedback via LED (option)

By means of several LEDs, warnings, error notifications and other information can be indicated – a considerable increase in safety.

Carrying methods:



Belt clip.



Optional:
shoulder strap, carrying bag.

Applications:

Industrial cranes, machinery and much more.



micron 5.

Further details:

- 10 two-step HBC push buttons plus rotary switch (inactive if not ordered) / STOP impact switch.
- LED for indication of operating / battery status.
- 2 rechargeable NiMH exchange batteries, approx. 30 hours of continuous operating time (standard version).
- Robust plastic housing, protection class IP 65.
- Weight: 550 g (1.2 lbs.) including battery and rubber shock absorber.
- Manual frequency switch.
- Further options: radiomatic® AFS (Automatic Frequency Selection), DECT, catch-release, tandem operation, radiomatic® infrakey, radiomatic® shock-off / zero-g (roll-detect in preparation), preselection of trolley / hoist, customized labeling by laser.